

ARPET COVER FR

FIRE RETARDANT CARPET COVER



PRODUCT DESCRIPTION

This fire retardant carpet protection film is amazingly strong, durable, puncture and tear resistant. High tech, water based adhesive system has major benefits over solvent-based systems in that it won't discolor or dye the carpets, and it has a clean release for easy removal without adhesive transfer. Contractors prefer Americover's Carpet Cover because of it's high strength quality and outstanding performance on the job.

APPLICATIONS

- **Model Homes**
- Moving
- Trade shows
- **Exhibitions**
- Remodeling
- **Dust Control**
- High traffic carpet protection
- Maintenance & repair
- Applications that require fire retardant materials

PRODUCT USE

Americover recommends that all products be stored and applied indoors at room temperature 60°-80° F (16°-17° C) and that relative humidity levels be kept between 30% - 70%. All products should be rotated so the "first-in, first-out" inventory method is utilized. For best results products should be applied to a clean, dry surface. It is best for the purchaser to test the suitability of our products under their unique conditions.

SIZE AND PACKAGING

WIDTHS LENGTHS

36", 48" 500'

PROPERTIES	TEST METHOD	VALUES
Film Backing		Linear Low Density Polyethylene (LLDPE)
Gauge	ASTM D3652	3 mil (0.003")
Tensile Strength	ASTM D882	3200 psi (md)
Elongation at Break	ASTM D882	500% (md)
Adhesion (oz/inch at 180°)	Modified PSTC #1	30.0
Adhesive Color		Water Clear
Fire Retardancy	NFPA 701	PASS

NOTE: The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use. SG.060717.021318





