



VAPORBLOCK® PLUS™

20 MIL VAPOR RETARDER/ GAS BARRIER



PRODUCT DESCRIPTION

VaporBlock® Plus™ 20 Mil Vapor Retarder/Gas Barrier is a seven-layer co-extruded barrier made from state-of-the-art polyethylene and EVOH resins to provide unmatched impact strength as well as superior resistance to gas and moisture transmission. VaporBlock® Plus™ is a highly resilient underslab / vertical wall barrier designed to restrict naturally occurring gases such as radon and/or methane from migrating through the ground and concrete slab. VaporBlock® Plus is more than 100 times less permeable than typical high-performance polyethylene vapor retarders against Methane, Radon and other harmful VOCs.

VaporBlock® Plus™ 20 Mil Vapor Retarder/Gas Barrier is one of the most effective underslab gas barriers in the building industry today far exceeding ASTM E-1745 (Plastic Water Vapor Retarders Used in Contact with Soil or Granular Fill Under Concrete Slabs) Class A, B and C requirements. Available in a 20 (Class A) mil thicknesses designed to meet the most stringent requirements. VaporBlock® Plus™ is produced within the strict guidelines of our ISO 9001:2008 Certified Management System.

APPLICATIONS

- ▶ Radon Barrier
- ▶ Methane Barrier
- ▶ VOC Barrier
- ▶ Under-Slab Vapor Retarder
- ▶ Foundation Wall Vapor
- ▶ Retarder

PRODUCT USE

VaporBlock® Plus™ resists gas and moisture migration into the building envelop when properly installed to provide protection from toxic/harmful chemicals. It can be installed as part of a passive or active control system extending across the entire building including floors, walls and crawl spaces. When installed as a passive system it is recommended to also include a ventilated system with sump(s) that could be converted to an active control system with properly designed ventilation fans.

VaporBlock® Plus™ works to protect your flooring and other moisture-sensitive furnishings in the building's interior from moisture and water vapor migration, greatly reducing condensation, mold and degradation.

SIZE AND PACKAGING

VaporBlock® Plus™ is available in 10' x 150' rolls to maximize coverage. All rolls are folded on heavy-duty cores for ease in handling and installation. Other custom sizes with factory welded seams are available based on minimum volume requirements. Installation instructions and ASTM E-1745 classifications accompany each roll.

VAPORBLOCK® PLUS™

SPECIFICATIONS

		VBLOCK20PLUS	
PROPERTIES	TEST METHOD	IMPERIAL	METRIC
Appearance		White/Gold	
Thickness, Nominal		20 mil	0.51 mm
Weight		102 lbs/MSF	498 g/m ²
Classification	ASTM E 1745	CLASS A, B & C	
³ Tensile Strength	ASTM E 154 Section 9 (D-882)	58 lbf	102 N
Impact Resistance	ASTM D 1709	2600 g	
Permeance (new material)	ASTM E 154 Section 7 ASTM E 96 Procedure B	0.0098 Perms grains/(ft ² ·hr·in·Hg)	0.0064 Perms g/(24hr·m ² ·mm Hg)
Permeance (after conditioning) (same measurement as above permeance)	ASTM E 154 Section 8, E96 Section 11, E96 Section 12, E96 Section 13, E96	0.0079 0.0079 0.0097 0.0113	0.0052 0.0052 0.0064 0.0074
WVTR	ASTM E 96 Procedure B	0.0040 grains/hr·ft ²	0.0028 gm/hr·m ²
Benzene Permeance	See Note ⁶	1.57E-10 m/s	
Toluene Permeance	See Note ⁶	2.18E-10 m/s	
Ethylbenzene Permeance	See Note ⁶	1.71E-10 m/s	
M & P-Xylenes Permeance	See Note ⁶	1.62E-10 m/s	
O-Xylene Permeance	See Note ⁶	1.53E-10 m/s	
Radon Diffusion Coefficient	K124/02/95	< 1.1 x 10 ⁻¹³ m ² /s	
Methane Permeance	ASTM D 1434	3.68E-12 m/s Gas Transmission Rate (GTR): 0.32 mL/m ² ·day·atm	
Maximum Static Use Temperature		180° F	82° C
Minimum Static Use Temperature		- 70° F	- 57° C

³ Tests are an average of machine and transverse directions.
6 Aqueous Phase Film Permeance.
Permeation of Volatile Organic Compounds through EVOH Thin Film Membranes and Coextruded LLDPE/EVOH/LLDPE Geomembranes, McWatters and Rowe, Journal of Geotechnical and Geoenvironmental Engineering[®] ASCE/September 2015. (Permeation is the Permeation Coefficient adjusted to actual film thickness)

VaporBlock[®] Plus™ Placement
All instructions on architectural or structural drawings should be reviewed and followed. Detailed installation instructions accompany each roll of VaporBlock[®] Plus™. ASTM E-1643 also provides general installation information for vapor retarders.

VaporBlock[®] Plus™ is a seven-layer co-extruded barrier made using high quality virgin-grade polyethylene and EVOH resins to provide unmatched impact strength as well as superior resistance to gas and moisture transmission.

NOTE: The information provided herein is based upon data believed to be reliable. All testing is performed in accordance with ASTM standards and procedures. All values are typical and nominal and do not represent either minimum or maximum performance of the product. Although the information is accurate to the best of our knowledge and belief, no representation of warranty or guarantee is made as to the suitability or completeness of such information. Likewise, no representation of warranty or guarantee, express or implied, or merchantability, fitness or otherwise, is made as to product application for a particular use.

RI.070116.020618